



Csi 3 HVP



CS 75V

CONTINUOUS SEALERS

To seal different types of pre filled flexible bags continuously. Applications in various industries like food processing, chemicals engineering....

Features

| Adjustable temperature /micro controller models suitable for a wide spectrum of materials | Variable speed conveyor | Vertical /Horizontal mountable models | H- Horizontal model | HV- Convertible into horizontal or vertical | V- Vertical model | CS PID ($\pm 8^{\circ}\text{C}$)-suitable for laminates | CS Digital ($\pm 4^{\circ}\text{C}$)-suitable for laminates | CSi ($\pm 2^{\circ}\text{C}$)-micro-controller based sealer (suitable for wide spectrum of materials) | CS Dual Sensor ($\pm 1^{\circ}\text{C}$) micro-controller based sealer (suitable for wide spectrum of materials)



CS 3 H



Csi 30V

TECHNICAL SPECIFICATIONS

Model	Sealing Width up to (mm)	Available conveyor load capacity	Power
CS PID (H/HV)	12	3 Kg, 15 Kg, 30 Kg,	240V
CS Digital (H/HV)	12	3 Kg, 15 Kg	240V
CSi (H/HV)	12	3 Kg, 15 Kg	240V
CS Dual Sensor (H/HV)	12	3 Kg	240V

*Horizontal model available only in 3 Kg